

# Technical data sheet

## **SIGA-Primur<sup>®</sup>** cartridge / tubular bag



**Updated on:** 30/12/2016

**Distributor:** SIGA Cover, Inc.

**Type of application:** durably airtight and windtight joints to plastered masonry and other mineral substrates

**Instructions:** see manual

**Composition:** high-performance adhesive compound, permanently strong adhesion and elasticity

**Packaging unit:** 12 cartridges, 12 tubular bags / box

### Characteristics:

	Standards	Units	Values
<b>Contents</b>	cartridge	310 ml 10.48 fl oz	Sufficient for 6 – 8 m Sufficient for 19 – 26 ft
	tubular bag	600 ml 20.29 fl oz	Sufficient for 12 – 16 m Sufficient for 39 – 52 ft
<b>Temperature resistance</b>		°C °F	-40 °C to +100 °C -40 °F to +212 °F
<b>Processing temperature</b>		°C °F	from +5 °C from +41 °F
<b>Diffusion-equivalent air layer thickness <math>s_d</math> / water vapor transmission: (for 4 mm bead thickness)</b>	EN 1931	m US perms	4 0.86
<b>Ageing resistance</b>	high permanent adhesive strength, non-drying and non-embrittling since without caoutchouc, resin or solvent, can reliably and durably follow structural movements		
<b>Suitability for storage</b>	frost-protected, unlimited		