

Zenith Series ZR-6 / 625



Zenith Series ZR-6 / 625 Windows and Doors

Alpen's Zenith Series ZR-6 fiberglass windows and doors deliver excellence in efficiency, comfort, durability and style. Combining the strength of high-quality pultruded fiberglass frames with the super-insulating power of suspended film Alpenglass ™, Zenith Series ZR-6 / 625 achieves both industry-leading thermal performance and commercial-grade structural capabilities. Offering monumental sizes, limitless styles and an accessible price point, the ZR-6 / 625 line is one of the most versatile high performance windows on the market.

Benefits:

- NFRC whole-window ratings up to R-6.3 (U-0.16)
- Center-of-glass performances from R-7.4 (U-0.14) to R-8.2 (U-0.12)
- Powered by super-insulating triple-pane suspended film Alpenglass
- Multiple glazing options for climate-responsive design
- Superior air and water infiltration resistance
- Dramatic noise reduction
- AAMA certified for residential, commercial, industrial and multifamily applications
- Custom-built to order in wide range of architectural styles, colors and accessories





Zenith Series ZR-6/625



TECHNICAL SPECIFICATIONS

Closed cell foam insulation Dual-sealed perimeter Inert gas fill Suspended coated film Insulated glass triple-pane High strength, low conductivity Wet and dry glazing sealants Triple weatherstrip on casements and awnings.

Zenith Series ZR-6 / 625 Full Frame NFRC Thermal Performance:

S tyles	Alpenglass Balanced-6				Alpenglass SolarControl-6				Alpenglass HighGain-6			
	U-factor	R-value	SHGC	VT	U-factor	R-value	SHGC	VT	U-factor	R-value	SHGC	VT
Fixed Low Profile	0.16	6.3	0.30	0.49	0.17	5.9	0.22	0.51	0.18	5.6	0.48	0.62
Fixed High Profile	0.16	6.3	0.27	0.44	0.17	5.9	0.20	0.45	0.17	5.9	0.43	0.56
Casement	0.19	5.3	0.24	0.38	0.20	5.0	0.17	0.39	0.20	5.0	0.38	0.48
Awning	0.19	5.3	0.24	0.38	0.20	5.0	0.17	0.39	0.20	5.0	0.38	0.48
Single Hung	0.19	5.3	0.26	0.42	0.19	5.3	0.19	0.43	0.20	5.0	0.41	0.53
Double Hung	0.21	4.8	0.25	0.40	0.21	4.8	0.18	0.41	0.22	4.5	0.39	0.50
Horizontal Sliding	0.19	5.3	0.27	0.43	0.19	5.3	0.19	0.44	0.20	5.0	0.42	0.54
Sliding Glass Door	0.20	5.0	0.27	0.43	0.21	4.8	0.19	0.44	0.21	4.8	0.41	0.53

DESIGNING WITH ALPENGLASS:

Alpenglass Balanced

Optimal blend of low U-factor and moderate solar control, a well-rounded solution for high performance homes in all climates

Alpenglass SolarControl


Extra protection against unwanted solar gain to keep spaces cool in summer and swing seasons, ideal for West- and South-facing windows in most climates

Maximum light and solar heat gain, ideal for passive solar homes and North-facing and well-shaded windows Alpenglass HighGain in spaces where more daylight is desired

WINDOW TYPES




Fixed Low Profile Fixed High Profile



Double weatherstrip on sliding, single and double hung windows.

Casement





Single Hung Awning Up to 60" x 36" Up to 55" x 91"



Double Hung



Horizontal Slider



Radius & Shapes



Sliding Patio Doors

Exterior Trim Accessories: Nailing Fin, Aluminum Brickmold, 3-1/4" and 2-5/8" Frame Extenders

Interior Trim Accessories: Jamb Extensions: 4-9/16", 6-9/16", Pine, Oak and Fir

SIMULATED DIVIDED LIGHTS

Zenith Series ZR-6 / 625 windows offer interior and exterior-applied Simulated Divided Light (SDL) Grids in classic styles and custom patterns.

Interior (Wood)

White

OReal metallic finish

Interior grille matches interior paint and color. For windows with interior wood veneer, grille arrives unfinished, ready to stain.

Contoured Grid Profile Widths: 7/8", 1-1/4" and 2"

Exterior (Aluminum)

Exterior grille matches exterior paint color.



Buffalo

Prairie



Double

Evergreen



Ladder

Faux Interlock

Custom

PAINT AND FINISH OPTIONS

Standard Colors: Casement, Awning, Picture Windows and Sliding Patio Doors

Bronze







Sandstone Silt



Red Rocks Flat Iron

Beige Coppertone Chestnut Black

¹ Decorative metal upgrades are real metals with "living" finish, patina may change with age



Oil Rubbed

*Vertical Grain Fir not available on sliding windows or doors