

Zenith Series ZR-7 / 725



Zenith Series ZR-7 / 725 Windows and Doors

Alpen's Zenith Series ZR-7 fiberglass windows and doors deliver beauty, comfort and long-lasting durability. Triple-pane suspended film glazing offers superior insulation in a range of solar and light gain configuration levels to satisfy many high performance home designs. When used in conjunction with tight envelope construction and smart weatherization practices, ZR-7 / 725 windows and doors can help lower energy use by preventing heat loss and keeping indoor spaces comfortable without continuous HVAC system cycling.

Benefits:

- NFRC whole-window ratings up to R-7.1 (U-0.14)
- Center-of-glass performance up to R-9.1 (U-0.11)
- Industry-leading air and water infiltration resistance
- Glass with 99.5%+ UV blockage protects interior finishes
- Passive House Certified and Living Building Challenge Compliant options
- Custom-built with superior craftsmanship and quality to fit any budget and style
- Multiple triple-pane suspended film Alpenglass™ configurations engineered to ensure optimal radiant comfort, year-round







Zenith Series ZR-7/725



TECHNICAL SPECIFICATIONS

Zenith Series ZR-7 / 725 Full Frame NFRC Thermal Performance:



S tyles	Alpenglass Balanced-7				Alpenglass SolarControl-7				Alpenglass HighGain-7			
	U-factor	R-value	SHGC	VT	U-factor	R-value	SHGC	VT	U-factor	R-value	SHGC	۷T
Fixed Low Profile	0.15	6.7	0.30	0.49	0.16	6.3	0.22	0.51	0.16	6.3	0.48	0.62
Fixed High Profile	0.14	7.1	0.27	0.44	0.15	6.7	0.19	0.45	0.15	6.7	0.43	0.56
Casement	0.18	5.6	0.24	0.38	0.18	5.6	0.17	0.39	0.19	5.3	0.38	0.48
Awning	0.18	5.6	0.24	0.38	0.18	5.6	0.17	0.39	0.19	5.3	0.38	0.48
Single Hung	0.18	5.6	0.26	0.42	0.19	5.3	0.19	0.43	0.19	5.3	0.41	0.53
Double Hung	0.20	5.0	0.25	0.40	0.21	4.8	0.18	0.41	0.21	4.8	0.39	0.50
Horizontal Sliding	0.18	5.6	0.27	0.43	0.19	5.3	0.19	0.44	0.19	5.3	0.42	0.54
Sliding Glass Door	0.19	5.3	0.26	0.43	0.19	5.3	0.19	0.44	0.20	5.0	0.41	0.53

DESIGNING WITH ALPENGLASS:

Alpenglass Balanced

Optimal blend of low U-factor and moderate solar control, a well-rounded solution for high performance homes in all climates

Alpenglass SolarControl


Extra protection against unwanted solar gain to keep spaces cool in summer and swing seasons, ideal for West- and South-facing windows in most climates

Alpenglass HighGain


Maximum light and solar heat gain, ideal for passive solar homes and North-facing and well-shaded windows in spaces where more daylight is desired

WINDOW TYPES





single and double hung windows













Fixed Low Profile

Fixed High Profile Up to 72" x 96"

Up to 36" x 72"

Awning Up to 60" x 36"

Single Hung Up to 55" x 91"

Double Hung Up to 55" x 91"

Horizontal Slider Up to 55" x 91"

Radius & Shapes

Sliding Patio Doors XO, XOO, OXXO

Exterior Trim Accessories: Nailing Fin, Aluminum Brickmold, 3-1/4" and 2-5/8" Frame Extenders

Interior Trim Accessories: Jamb Extensions: 4-9/16", 6-9/16", Pine, Oak and Fir

SIMULATED DIVIDED LIGHTS

 $Zenith\ Series\ ZR-7\ /\ 725\ windows\ offer\ interior\ and\ exterior-applied\ Simulated\ Divided\ Light\ (SDL)\ Grids$ in classic styles and custom patterns.

Interior grille matches interior paint and color. For windows with interior wood veneer, grille arrives unfinished, ready to stain.

Exterior (Aluminum)

Exterior grille matches exterior paint color.







Double



Ladder



Custom

Brushed

Antique Brass†

Contoured Grid Profile Widths: 7/8", 1-1/4" and 2"

PAINT AND FINISH OPTIONS







Sandstone Silt



